1) Se debe incorporar el IVA **19%** e Impuesto aduanero **6%.**
2) No Aplica el **6%** en caso de contar con certificado de origen, lo que se suma al costo **(USD 40 o USD 50)**
3) Se debe incluir servicio de traslado cuyo costo es de **CLP$300.000 xMt3**
4) Por cada pedido la orden minima dependera de que si el producto se encuentra en stock.
5) Cantidad minima por producto son 10 Unidades, el proveedor permite compras menores solo si se encuentran en stock

Generadores

Picture	Item Model	Product Description	Panel	Precio
		Silent		
	**DP2750IS-C**	Rated voltage/Fre: 220V/ 50Hz, Rated Power: 1.8 KW Max. output power: 2.0KW Alternator: Copper ; Starting system: Recoil Fuel tank capacity: 5L, Oil capacity: 450ML Engine: 148F/79.7CC/48*35mm, Type: Single Cylinder, 4 Stroke, Air foce cooling, OHV standard panel: Panel with a manual switch , with ESC switch, with 1*16A socket with 3-in-1 indicator light (overload + output + oil alarm light) Package size:525X335X545 Net/gross weight: 19/21		229.000
	**DP4500IS-K2**	Rated voltage/Fre: 220V/ 50Hz, Rated Power: 3.5 KW Max. output power: 3.8KW Alternator: Copper ; Starting system optional: Recoil/E-start/Remote start Fuel tank capacity: 9L, Oil capacity: 550ML Engine: 166F/153CC/65mm×54 mmmm, Engine style:Single Cylinder, 4 Stroke, Air foce cooling, OHV standard panel: Panel with a manual switch , with ESC switch, with 1*16A socket with 3-in-1 indicator light (overload + output + oil alarm light) Package size540x355x570 Net/gross weight: 23/25		408.000

	**DP4000iO-A**	Rated voltage/Fre: 220V/ 50Hz, Rated Power: 3.0KW Max. output power: 3.5KW Alternator: Copper ; Starting system: Recoil start Ignition: T.C.I Fuel tank capacity: 3.5L, Oil capacity: 600ML Engine: 212F/212CC/70mm*55mm, Package size: 512×364×450 Net/gross weight: 27/29 Panel:with a manual switch , with reset switch, with 1*16A socket X2,with 3-in-1 indicator light (overload + output + oil alarm light)		172.000
	**DP5000iO-F2**	Rated voltage/Fre: 220V/ 50Hz, Rated Power: 4.0KW Max. output power: 4.5KW Alternator: Copper ; Starting system: Recoil start Ignition: T.C.I Fuel tank capacity: 7L, Oil capacity: 600ML Engine: 225F/223CC/72mm*59mm, Package size: 540x440x475 Net/gross weight: 29/31 Panel:with a manual switch , with reset switch, with 1*16A socket X1,with 3-in-1 indicator light (overload + output + oil alarm light)		230.000
	**DP6500IO-H**	Rated voltage/Fre: 220V/ 50Hz, Rated Power: 5.0KW Max. output power: 5.5KW Alternator: Copper ; Starting system: Recoil start Ignition: T.C.I Fuel tank capacity: 10L, Oil capacity: 600ML Engine: 240F-V/240CC/72mm*59mm, Package size: 545x445x475 Net/gross weight: 29/31 Panel:with a manual switch , with reset switch, with 1*16A socket X1,with 3-in-1 indicator light (overload + output + oil alarm light)		283.000